

## GR/GP用基礎ブロック

W	×	L	×	H	φ	質量	製造形態		備考		
							センター	偏芯及びかぶり			
歩車B型片R 300 × 300 ×				600	100	116	受注		無筋		
400	×	400	×	400	150	138	受注	受注	50		
				450		155					
				500		172					
				600		207					
				700		241	標準				
				800		276					
400	×	600	×	400	200	202	受注	受注	W方向 50		
				500		252	標準				
				600		303					
				700		353	受注				
				800		404					
400	×	800	×	400	150	293	受注				
				500		366					
				600		439					
400	×	1000	×	400	200	357	受注	受注	W方向 50 L方向 可能		
				500		446	標準				
				600		535	受注				
				700		624					
				800		714					
400	×	1300	×	500	200	591	受注				
				600		709					
400	×	1400	×	400	200	512	受注				
				500		640	標準				
				600		768	受注				
400	×	1500	×	400	180	556	受注				
				500		695					
				600		834					
400	×	3000	×	400	180	1112	受注			2つ穴 間隔2m	
				450		1251					
				500		1390					
500	×	500	×	500	210 /180	274	受注			無筋	
				600		334					
500	×	800	×	400	180	363	受注	受注	L方向 50		
				500		453					
				600		544					
500	×	1000	×	400	200	454	受注	受注	W方向 50 L方向 可能		
				450		510					
				500		567					
				600		680					

W	×	L	×	H	φ	質量	製造形態		備考	
							センター	偏芯及びかぶり		
600	×	1000	×	450	180	626	受注		仮設専用	
(国土交通省タイプ)										
600	×	1500	×	400	180	847	受注			
				500						1058
				600						1270
600	×	2000	×	400	180	1137	受注			
				500						1421
				600						1705
800	×	800	×	450	150	678	受注	受注   150	仮設専用	
800	×	1500	×	400	200	1131	受注			
				500						1414
				600						1697