

照明灯用基礎ブロック

W	×	L	×	H	φ	質量	センター	偏芯	偏芯量 かぶり	埋設管対応 開口径	備考	
300	×	300	×	700	150	123	標準	標準	50	受注 50×100		
				800								
				900		受注	受注					
				1000								
アンカ・FEP仕様は、資材支給により製造可能												
400	×	400	×	700	200	241	標準	受注	50	受注 100×150		
				800								
				900								
				1000		受注						
				1100								
				1200			413					標準 100×150
アンカ・FEP仕様は、資材支給により製造可能												
500	×	500	×	800	250	389	標準	標準	50	受注 100×150		
				900								
				1000								
				1100		受注		標準 100×150				
				1200		標準						
				1300								
				1400								
				1500		受注		受注 100×150				
				1600								
				1700								
				1800								
				1900								
				2000								
2100												
2400		1168										
アンカ・FEP仕様は、資材支給により製造可能												
600	×	600	×	1000	250	752	標準	受注	100	標準 100×200		
				1100								
				1200								
				1300								
				1400			1053			受注		受注 100×200
				1500			1129					
				1600			1204					
				1700			1279					
				1800			1354					
				1900			1430					
				2000			1505					
				2100			1580					
				2400			1806					
アンカ・FEP仕様は、資材支給により製造可能												
スパイラル管用 ねかせφ 490				300	250	113	標準					
				400		159	受注					